



QUICKFUGA

PRODUCT STRENGTHS

- Facilitates cleaning of covering materials
- Keeps the sponge cleaner
- Cleans thoroughly, no need to rinse
- Improves the surface finish of the grout
- Suitable for all surfaces.

AREAS OF USE

Use

Substrates:

- ceramic, porcelain tiles
- glass mosaic, marble and natural stone

INSTRUCTIONS FOR USE

Preparation of substrates

The coating materials must first be cleaned to remove any dust. QuickFuga must still be fresh.

Preparation

QuickFuga is a ready-to-use transparent fluid that can be diluted with water in any ratio.

Application

Begin cleaning the tilework when the grout is still fresh. On completion, pour quickfuga into the cleaning tray in the quantities indicated, then clean up the surface using a thick, large-sized damp sponge, preferably made of cellulose, to avoid removing grout from the joints. Use circular movements to soften the film of grout on the tiles and finish cleaning the joint surface. Specific high-dispersion polymers ensure all grout residues are removed using only a small amount of water. The use of an excessive amount of water when cleaning would impair the final chemical resistances. Rinse frequently and make sure clean water is used at all times, using appropriate trays and grills with cleaning rollers. If necessary, replace the sponge or felt cleaning pad when saturated with grout. Final cleaning should be done, by sponge applied in a diagonal directions to avoid material coming out from the joints. Wipe the cleaned surface again with a dry cloth to make sure it is completely clean and there are no streaks of resin remaining.

QUICKFUGA

Cleaning

Residues of quickfuga can be cleaned from tools by rinsing them thoroughly.

Technical Data	
Appearance	Transparent liquid
Specific weight	≈ 1 kg/dm ³
Shelf life	≈ 24 months in the original packaging
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Pack	3 Litre Plastic Pail
Water dilution ratios	ready to use
pH	≈ 7
Temperature range for application	from +5 °C to +35 °C
Coverage	≈ 100 – 200 m ² /1 ℓ
Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate and of the materials laid.	

WARNING

- Product for professional use
- abide by any standards and national regulations
- store and use at a temperature above +5 °C. Protect from frost
- do not leave cans or bottles open, even during use
- if necessary, ask for the safety data sheet